

**VISO FOLD 1000 BI-FOLD DOOR ORDER/QUOTE FORM**

Page \_\_\_ of \_\_\_.

Please tick for quote only

Aluminium Direct Fax: 01453 827801

E-mail Orders: ali.scheduler@customade.co.uk

Company Name (Acc No): \_\_\_\_\_

Signature: \_\_\_\_\_

Preferred Delivery Date: \_\_\_\_\_

Print Name: \_\_\_\_\_

Date: \_\_\_\_\_ E-mail confirmation: \_\_\_\_\_

**Please Circle Items Required**

(Q) = Selection may need to be upgraded to meet Part Q

**Part Q Compliant:** Y / N

**Colour:** White (G) / Grey (7016M) / Black (9005M) /

Dual Grey Ext (M) & White Int (G)

**Master Door Handle:** Lever-Lever only

**Slave Door Handle** (if applicable): Lever-Lever / Intermediate  
(Shootbolt)

**Intermediate Handles:** Locking / Non-Locking

**Lever-Lever Handle Colour:** White / Black / Chrome

Grey / Graphite / Satin Silver / Gold

**Intermediate Handle Colour:** White / Black / Chrome / Grey

**Hinge Colour:** White / Black (recommended)

**'D' Pull Handle** (on hinge): White / Black (recommended) / Chrome / Grey

**Nickel Cylinder**<sup>(Q)</sup>: STD Key-Key / STD Thumbturn

3\* Security Key-Key / 3\* Security Thumbturn  
(T/turn n/a on intermediate handles, 3\* not keyed alike)

**Magnetic Hold Open Catch:** None / White / Black /  
 Grey / Chrome

**Trickle Vent:** None / White / Black / Grey / Silver  
 Grey on White

**Glass Supply:** Hourglass / Unglazed

**Glass Spec** (Cl tgh, Softcoat, Argon, Black W/edge)<sup>(Q)</sup>:

28mm DGU / 36mm TrGU

**Glass Special Requirements:** \_\_\_\_\_

**Threshold:** [ ] DV14 50mm rebated

[ ] DV171 15mm flush Ramp: Inside / Outside

[ ] DV173 20mm flush Ramp: Inside / Outside

[ ] DV175 30mm flush

**Deliver:** Assembled / Flat pack frame sashes

Note: flush thresholds not weather rated

**Note:** Mullion dimensions can vary depending on style. External access is only available on bi-folds which have a 'lead' door.

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Qty	Cill	Sizes (mm) Including Cills & Add-ons	20mm Add-ons (required with t/vents)	Special Requirements
	Open in / Open out			None	W (max 1200mm per sash)	T	
				85		B	
				150	H (max 2500mm)	L	
				190 / 225		R	
	Open in / Open out			None	W (max 1200mm per sash)	T	
				85		B	
				150	H (max 2500mm)	L	
				190 / 225		R	
	Open in / Open out			None	W (max 1200mm per sash)	T	
				85		B	
				150	H (max 2500mm)	L	
				190 / 225		R	