

VISO FOLD 1000 BI-FOLD DOOR ORDER/QUOTE FORM

Aluminium Direct Fax: 01453 827801

E-mail Orders: ali.scheduler@customade.co.uk



Please tick for quote only

Page ___ of ___.

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q	
<p>Part Q Compliant: Y / N</p> <p>Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ext (M) & White Int (G)</p> <p>Master Door Handle: Lever-Lever only</p> <p>Slave Door Handle (if applicable): Lever-Lever / Intermediate</p> <p>Intermediate Handles: Locking / Non-Locking</p> <p>Lever-Lever Handle Colour: White / Black / Chrome / Grey / Graphite / Satin Silver / Gold</p> <p>Intermediate Handle Colour: White / Black / Chrome / Grey</p> <p>Hinge Colour: White / Black (recommended)</p> <p>'D' Pull Handle (on hinge): White / Black (recommended) / Chrome / Grey</p> <p>Nickel Cylinder^(Q): STD Key-Key / STD Thumbturn / 3* Security Key-Key / 3* Security Thumbturn (T/turn n/a on intermediate handles, 3* not keyed alike)</p>	<p>Magnetic Hold Open Catch: None / White / Black / Grey / Chrome</p> <p>Trickle Vent: None / White / Black / Grey / Silver</p> <p>Glass Supply: Hourglass / Unglazed</p> <p>Glass Spec (Cl tgh, Softcoat, Argon, Black W/edge)^(Q): 28mm DGU / 36mm TRGU</p> <p>Glass Special Requirements: _____</p> <p>Threshold: [] DV14 50mm rebated [] DV171 15mm flush Ramp: Inside / Outside [] DV173 20mm flush Ramp: Inside / Outside [] DV175 30mm flush</p> <p>Deliver: Assembled / Flat pack frame sashes</p> <p>Note: flush thresholds not weather rated</p>

Note: Mullion dimensions can vary depending on style. External access is only available on bi-folds which have a 'lead' door.

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Cill	Sizes (mm) Including Cills & Add-ons		20mm Add-ons (required with t/vents)		Special Requirements
				W	H	T	B	
	Open in / Open out		None 85 150 190 / 225	(max 1200mm per sash)	(max 2500mm)	T	B	
	Open in / Open out		None 85 150 190 / 225	(max 1200mm per sash)	(max 2500mm)	T	B	
	Open in / Open out		None 85 150 190 / 225	(max 1200mm per sash)	(max 2500mm)	T	B	