

**VISOGLIDE PLUS ORDER/QUOTE FORM**

Please tick for quote only

Page \_\_\_ of \_\_\_

Aluminium Direct Fax: 01453 827801 E-mail Orders: ali.scheduler@customade.co.uk

Company Name (Acc No): \_\_\_\_\_

Signature: \_\_\_\_\_

Preferred Delivery Date: \_\_\_\_\_

Print Name: \_\_\_\_\_

Date: \_\_\_\_\_ Contact Numbers: \_\_\_\_\_

Please fax / e-mail confirmation to: \_\_\_\_\_

**Please Circle Items Required**

**Part Q Compliant:** Y / N

(If yes, rollers and locks will be upgraded at an additional charge)

**Outer frame:** Standard / Internal upstand

**Colour:** White (G) / Grey (7016M) / Black (9005M) /  
 Dual Grey Ex (M) & White Int (G)

**Wind loading reqd:** None (<800pa) / Light (<1000pa) / Heavy (<1250pa) / Severe (<1500pa)

**Glass Supply:** Hourglass / Unglazed

**Std Glass Spec:** 4mm tgh / 6mm tgh / 8mm tgh  
 28mm DGU / 36mm TGU

(Q) = Selection may need to be upgraded to meet Part Q

**Cill:** None / Two Track 190mm / Three Track 235mm

**Handle Type:** D / Lever-Lever  
 Internal Only / Internal & External

**Handle Colour:** White / Black / Grey / Satin Silver  
 (Note: Chrome n/a)

**Nickel Cylinder<sup>(Q)</sup>:** STD Key-Key / STD Thumb Turn  
 3\* Security Key-Key / 3\* thumb Turn

**Trickle Vent(s) fitted in 42mm add-on:** QTY [ ]

**Trickle Vent Size:** 1250 / 2500 / 5000

**Colour:** None / White / Black / Grey / Silver /  
 Grey on White

If the required products are over 4m in width or 2.2m in height:

**Deliver:** Assembled (chargeable) / Assembled (FOC)\*  
 / Flat packed

\*You will need to ensure able bodied people are available to assist with offloading at the delivery address. If this requirement is not met you will be charged for the redelivery of the product.

**Interlocking Mullion:** Standard 83mm / Slim 35mm  
 (Additional lead time may apply)

**Key Limits**

Max sash width for 4mm tgh = 1400mm (approx)

Max sash width for 6mm tgh = 1700mm (approx)

Max sash height = 2500mm

Max sash weight = 200kg

Wind loadings may require heavy duty mullions.

**Please indicate style by ticking box** ('H' indicates handle position)

Interlocking mullion      Bi-parting mullion

As shown       As shown       Reverse

As shown       Reverse       As shown       Reverse

As shown       Reverse       As shown       Reverse

As shown       Reverse

As shown       Reverse

Qty	Sizes (mm) Including Cills & Add-ons	42mm Add-ons (required with t/vents)	Special Requirements
	W	T	
		B	
		L	
	H (max 2500mm)	R	
		L	
		R	
	W	T	
		B	
		L	
	H (max 2500mm)	R	
		L	
		R	