

VISO FOLD 1000 BI-FOLD DOOR ORDER/QUOTE FORM



Page

Aluminium Direct Fax: 01453 827801

E-mail Orders: ali.scheduler@customade.co.uk

Please tick for quote only

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Please Circle Items Required

<p>(Q) = Selection may need to be upgraded to meet Part Q</p> <p>Part Q Compliant: Y / N</p> <p>Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ext (M) & White Int (G)</p> <p>Master Door Handle: Lever-Lever only</p> <p>Slave Door Handle (if applicable): Lever-Lever / Intermediate (Shootbolt)</p> <p>Intermediate Handles: Locking / Non-Locking</p> <p>Lever-Lever Handle Colour: White / Black / Chrome Grey / Graphite / Satin Silver / Gold</p> <p>Intermediate Handle Colour: White / Black / Chrome / Grey</p> <p>Hinge Colour: White / Black (recommended)</p> <p>'D' Pull Handle (on hinge): White / Black / Chrome / Grey (recommended)</p> <p>Nickel Cylinder^(Q): STD Key-Key / STD Thumbturn 3* Security Key-Key / 3* Security Thumbturn (T/turn n/a on intermediate handles, 3* not keyed alike)</p>	<p>Magnetic Hold Open Catch: None / White / Black / Grey / Chrome</p> <p>Trickle Vent: None / White / Black / Grey / Silver Grey on White</p> <p>Glass Supply: Hourglass / Unglazed</p> <p>Glass Spec (Cl tgh, Softcoat, Argon, Black W/edge)^(Q): 28mm DGU / 36mm TrGU</p> <p>Glass Special Requirements: _____</p> <p>Threshold: [] DV14 50mm rebated [] DV171 15mm flush Ramp: Inside / Outside [] DV173 20mm flush Ramp: Inside / Outside [] DV175 30mm flush</p> <p>If the required products are over 4m in width or over 2.2m in height:</p> <p>Deliver: Assembled (chargeable) / Assembled (FOC)* / Flat packed</p> <p>*You will need to ensure able bodied people are available to assist with offloading at the delivery address. If this requirement is not met you will be charged for the redelivery of the product.</p> <p>Note: flush thresholds not weather rated</p>
--	---

Note: Mullion dimensions can vary depending on style. External access is only available on bi-folds which have a 'lead' door.

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Qty	Cill	Sizes (mm) Including Cills & Add-ons		20mm Add-ons (required with t/vents)		Special Requirements
					W	H	T	B	
	Open in / Open out			None 85 150 190 / 225	W (max 1200mm per sash)	H (max 2500mm)	T B L R		
	Open in / Open out			None 85 150 190 / 225	W (max 1200mm per sash)	H (max 2500mm)	T B L R		
	Open in / Open out			None 85 150 190 / 225	W (max 1200mm per sash)	H (max 2500mm)	T B L R		